

GLECO TRAP

4 STEP INSTALLATION GUIDE



INSTALLATION (UKST018 SEDIMENT TRAP KIT)

The UKST018 Compact 1.8 Litre Sediment Trap Package is supplied complete with the following materials to aid with installation:

- (1) 1 1/2" x 7" sink tailpiece
- (1) 1 1/2" trap tailpiece
- (2) 1 1/2" slip-joint washers
- (4) 1 1/2" slip-joint nuts
- (1) 1 1/2" flat washer
- (2) O-Ring
- Complete instructions

IMPORTANT NOTES

Do not use this Sediment Trap in environments where very hot waste water is run directly to drain unless you are able to run cold water at the same time. Ideal maximum temperature of 38°C. Hot liquids and solids could potentially deform the plastic collector bottles and cause a leak.

When switching the bottles, make sure to smear a little petroleum jelly onto the top edge of the replacement bottle (not the threads) to prevent the rubber "O"-Ring from dragging and to help create a leak-free seal.

To see our complete product range, please visit
www.ukh2o.co.uk

Tel: 0845 1 700 500 • Fax: 01903 249 569

GLECO TRAP

2 MINUTE MAINTENANCE GUIDE



Maintenance is required when solids reach the designated fill line.



We recommend applying a small amount of Vaseline on the top of new bottle.



Place the new, empty bottle under the valve and open



The water in the upper portion of the trap will drain down....



... below the threads on the bottle,



allowing removal of first bottle with no chance of water spillage.



Then place the bottle with the drained water onto the body of the trap.



By closing the valve and placing lid on full bottle, maintenance is complete.

OTHER IMPORTANT MEASUREMENTS

Actual Measurements:

Bottles only without lid, from top of threads to bottom (some are slightly rounded up to nearest discernable mm).

0.5 Litre = 102mm

0.9 Litre = 166mm

1.2 Litre = 127mm

1.8 Litre = 185mm

3.7 Litre = 248mm

127mm = Widest diameter of 1.8 litre bottle

140mm = Height of Sediment Trap without bottle installed from top of the threads that attach to the sink pipe to the bottom of the trap.

318mm = Physical height of ST18 (with bottle installed) from top of the threads that attach to the sink pipe to the bottom of the bottle. The top of the threads to the drain pipe are slightly lower.

267mm = width of the Sediment Trap from the outer edge of the sink pipe to the outer edge of the valve stem (left to right, as it appears in photos). This width is constant, regardless of bottle attached.

NOTE: Keep in mind that the bottles will need to unscrew from the Sediment Trap for replacement. Allow approximately 50mm of free space below to change bottles easily. UKST037 trap kits require support such as a baton or similar (not supplied).