



## UKST030SS (3 Litre) Stainless Steel Sediment Trap Specification, Installation & Maintenance Guide



### Dimensions:

Minimum Height including Inlet & Outlet Fittings:	235mm
Diameter (Collector Body Only):	174mm

### Installation

The UKST030SS (3 Litre) Stainless Steel Sediment Trap Kit is supplied with a universal 40mm outlet adaptor to fit most UK waste pipes. The trap screws directly on to the sink outlet spigot - The trap body is easily separated from the lid once the two sealing clamps are undone. Silicone grease or Vaseline may be required in order to keep the seal in good condition & to ease separation of the two body parts for on-going maintenance.

<b>TRAP INLET:</b>	USE PTFE TAPE AS REQUIRED
<b>TRAP OUTLET:</b>	1½" Adaptor 40mm Universal Compression Coupler

Use the appropriate jointing materials & compounds; PTFE Tape, solvent weld cleaner & adhesive following the relative manufacturers instructions.

These jointing materials are not supplied with your sediment trap kit.

All fittings are supplied loose for ease of installation; Failure to use the appropriate materials could result in water leaks.

Before filling the UKST030SS Trap, make sure all of the joints have been made correctly using the correct materials and where any adhesives have been applied, the correct amount of drying time has lapsed in accordance with the manufacturers' directions.

### Cleaning Instructions

- 1 To clean the trap; Place bowl beneath the trap.
- 2 Open both stainless steel clamps - The trap is now ready for removal for cleaning.
- 3 Ease the lower trap body gently down towards the bowl - The trap body must be moved / lifted in accordance with "Health & Safety" guidelines.
- 4 Clean out the trap appropriately, disposing of waste material in a responsible manner.
- 5 Reverse above steps to re-install the trap, periodically coating Vaseline or similar silicone grease (not silicone) on both sides of gasket to maintain a good seal.
- 6 Check for leaks.